Data Sheet for Article: AC20606031

Empty field Modul 2500TT, 1 door IP31, H=2000 W=600 D=600mm

sheet steel, RAL7035, four-point rod lock with push-pull handle

Technical Data

Net width (mm)	600,00
Net height (mm)	2.000,00
Netto depth (mm)	600,00
Net weight (kg)	105,80
Min. ambient temperature (°C)	-10
Max. ambient temperature (°C)	60
IP Rating	IP31
Protection class	I
Material	sheetsteel
Colour	RAL 7035 (Light grey)
Width (mm)	600
Height (mm)	2000
Depth (mm)	600
Corpus wall thickness (mm)	1,50
Door wall thickness (mm)	2
Load capacity per door (kg)	100
Number of doors	1

Created online on 2026-08-01, No liability for errors. All information subject to change.

/null

Get Ready. **Get Schrack.**

Technical Data - continued

Optional Accessories	ACSOT062--;ACSOB062--;ACPMP0806-;ACPMP0604-;AC2500BBW-;AC2500BBH-;AC2500BBD-;AC2500BH1-;AC2500BH2-;AC2500PE--;ACSOT062--;ACSOB062--;ACCLH600--;ACCLC400--;ACCLF200--;ACCAB600--;ACLE9301--;IL900415-F;ACTW2006--;ACSPDG01--;ASDRA400--

Article Table

DESCRIPTION	Order No.
Empty field Modul 2500TT, 1 door IP31, H=2000 W=600 D=600mm sheet steel, RAL7035, four-point rod lock with push-pull handle	AC20606031
Optional Accessories	
Plinth side parts (pair) with corner parts D=600 H=200 mm preassembled, sheet steel RAL9005 (Jet black)	ACSOT062
Plinth front and rear part W=600 H=200 mm sheet steel PU=2 pieces, RAL9005 (Jet black)	ACSOB062
AC/KC Partial mounting plate H=800mm (H=600mm horizontal) for enclosures T=600mm (W=800mm horizontal), applicable vertically and horizontally	ACPMP0806
AC/KC Partial mounting plate H=600mm (H=400mm horizontal) for enclosures T=400mm (W=600mm horizontal), applicable vertically and horizontally	ACPMP0604
Busbar holder, horizontal element (PU=6 Pieces)	AC2500BBW
Busbar holder, vertical element H=100mm (PU=6 Pieces)	AC2500BBH
Busbar holder spacer 9mm (PU=24 Pieces)	AC2500BBD
L-shaped mounting bracket for busbar holder	AC2500BH1
T-shaped mounting bracket for busbar holder	AC2500BH2
Z-shaped mounting bracket for PE rail	AC2500PE
Plinth side parts (pair) with corner parts D=600 H=200 mm preassembled, sheet steel RAL9005 (Jet black)	ACSOT062
Plinth front and rear part W=600 H=200 mm sheet steel PU=2 pieces, RAL9005 (Jet black)	ACSOB062
Mounting profiles for heavy load components (pair) L=600mm with mounting accessories	ACCLH600
Click-in profiles (pair) L=400mm with mounting accessories	ACCLC400
Mounting profiles (pair) L=2000mm with mounting accessories	ACCLF200
Cable fixing bars (pair) for 600mm wide enclosures	ACCAB600

Created online on 2026-08-01, No liability for errors. All information subject to change.

/null

Get Ready. **Get Schrack.**

Article Table

DESCRIPTION	Order No.
Optional Accessories	
Eye bolts M12 for lifting of AC and KC enclosures PU=4 pieces	ACLE9301
Cable entry gland plate (foam rubber) size 2 does not correspond to degree of protection IP2x-C	IL900415-F
Divider panel H=2000 D=600 mm galvanized sheet steel	ACTW2006
Gasket tape made of Polyethylene PE-01, IP55	ACSPDG01
Document pocket, self-adhesive and screwable, DIN A4	ASDRA400

Created online on 2026-08-01, No liability for errors. All information subject to change.

Get Ready. **Get Schrack.**