

Bollard light ALVA 940/ 170 OP 180° 600lm 840 MD IR DALI IP65

Diffuser: opal, graphite gray, protected from sea air, dirt-repellent thanks to powder coating with lotus effect, Integrated motion detector with DALI bus power supply, IR remote-controlled



Technische Daten

Net height (mm)	940,00
Net diameter (mm)	170,00
Net weight (kg)	7,83
Min. ambient temperature (°C)	-25
Max. ambient temperature (°C)	40
Luminaire type	bollard luminaire
Mounting	floor mounting
Colour	Grafit
Beam angle (°)	283
Operating voltage AC (V)	200-240
System efficiency (lm/W)	37
Power (W)	17
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	80
Colour stability MacAdam (sdcm)	1

Technische Daten - Fortsetzung

Luminous flux (lm)	630
Service life	70.000h (L80B50)
Dimmable	DALI yes
Protection class	1
IP Rating	IP65
Shock strength	IK09
Illuminant incl.	yes
ØxH mm	170x940

BEZEICHNUNG	BEST.NR.
Bollard light ALVA 940/170 OP 180° 600lm 840 MD IR DALI IP65	
Diffuser: opal, graphite gray, protected from sea air, dirt-repellent thanks to powder coating with lotus effect, Integrated motion detector with DALI bus power supply, IR remote-controlled	ESL820984