

Data Sheet for Article: EV103325--

Dimmer insert 3-350 VA, dimmable LED, incl. cover VISIO S 55

To be completed in VISIO S 55 DESIGN "CUBIC" with frame 1-gang EV105301-- , 2-gang EV105302-- , 3-gang EV105303--



Schrack-Info

LED-Drehdimmer mit Ein-/Aus-Taste. Durch das eingebaute Potentiometer kann eine Grundhelligkeit eingestellt werden, sprich ein konstanter Helligkeitswert, der bei jedem Einschalten gleich ist. Die Dimmerabdeckung ist bereits im Lieferumfang enthalten und muss somit nicht separat bestellt werden. Für den Anschluss ist kein Neutralleiter erforderlich.

Technical Data

Net width (mm)	71,00
Net height (mm)	71,00
Netto depth (mm)	42,00
Net weight (kg)	0,07
Series	01-VISIO S 55
Design	CUBIC
Product typ	Dimmer
Dimmertyp	Leading edge dimmer
Load type	Ohmic
	Capacitive

Technical Data - continued

Dimmable illuminants	Low voltage halogen lamp with electronic transformer Dimmable 230V LED lamp Incandescent lamp High voltage halogen lamp
Power range	3-350 W/VA
Operating voltage AC (V)	230
mounting	Screws and claws
Mounting method	Flush-mounted
Operating temperature	0°C to +35°C
IP Rating	IP20
Colour	White
Connection type	Terminal Block
Connection clamps	according to EN 60669-1
Allowed cables	Flexible with end splice Flexible Stiff
Allowed cross-section (mm²)	1,5 und 2,5
Material	ABS Galvanized steel
Environment	Halogen free
Sustainability	ROHS
test mark	VDE
Dimensions (mm)	71x71x42
Mounting Depth mm (mm)	35

DESCRIPTION	Order No.
Dimmer insert 3-350 VA, dimmable LED, incl. cover VISIO S 55	EV103325
To be completed in VISIO S 55 DESIGN "CUBIC" with frame 1-gang EV105301-- , 2-gang EV105302-- , 3-gang EV105303--	