

Data Sheet for Article: EV121362--

Pin compact socket outlet 2x2P+E, 45° turned, cage cla, silv

VISIO S 55 (55x55), Rated current 16A, Connection type Plug-in terminal, Silver



Technical Data

Net length (mm)	70,00
Net width (mm)	70,00
Net height (mm)	41,00
Net weight (kg)	0,11
Series	01-VISIO S 55
Design	CUBIC
Product typ	Shockproof socket
Operating voltage AC (V)	230
Rated current (A)	16
mounting	Screws and claws
Mounting method	Flush-mounted
IP Rating	IP20
Colour	Silver
Connection type	Plug-in terminal
Connection clamps	according to EN 60884-1
Allowed cables	Stiff
Allowed cross-section (mm²)	1,5 und 2,5

Technical Data - continued

Material	ABS
	Brass
	Galvanized steel
	Plastic
	Copper
Environment	Halogen free
Sustainability	ROHS
test mark	VDE
Dimensions (mm)	125x85x50
Mounting Depth mm (mm)	30

DESCRIPTION	Order No.
Pin compact socket outlet 2x2P+E, 45° turned, cage cla, silv	EV121362
VISIO S 55 (55x55), Rated current 16A, Connection type Plug-in terminal, Silver	