

Data Sheet for Article: H5ULY05K0Y

Patchcord RJ45 unshielded, Cat.5e, PVC, yellow, 5.0m



SCHRACK Info

Patchcords for generic, structured network cabling systems. Support all applications requiring Class D (e.g. 1000Base-T, 100Base-TX, ATM) as well as VoIP, PoE.

Patchcord with moulded boot in matching cable color. Pin assignment 1:1.

ISO/IEC 11801 2nd ed.; EN 50173-1 and IEC 61156-5.



Technical Data

Category	Cat.5e
Cable construction	4x2xAWG24/7
Cable shielding	U/UTP
Connection	1:1
Bit rate	up to Gigabit Ethernet
Number of pairs	4
Shielding	unshielded
Cable jacket	PVC
LED Functionality	without LED
Net weight (kg)	0,18

Technical Data - continued

Colour	Yellow
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	60
RoHS	conform
Patchcordlength (m)	5,0
Net width (mm)	230,00
Net height (mm)	170,00
Connector standard	EN 60603-7
Connector type	RJ45 unshielded
Pin assignment	EIA/TIA 568B 1:1
Packing	Single packed in polybag with label

Article Table

DESCRIPTION	NVP (%)	COPPER WEIGHT (kg/km)	Order No.
Patchcord RJ45 unshielded, Cat.5e, PVC, yellow, 5.0m			H5ULY05K0Y
Optional Accessories			
TOOLLESS LINE Jack RJ45 unshielded, Cat.5e (SFA)			HSEMRJ5UWS
Patchpanel 19" 24xRJ45 unshielded Cat.5e, 1U, RAL7035			HSERU245GF
Light grey			
Data Outlet 2xRJ45 unshielded Cat.5e, 80x80mm,angled,RAL9010			HSEDU2UW5F
Pure white			
U/UTP Cable Cat.5e, 4x2xAWG24/1, PVC, Eca, blue, Box 305m	69	15	HSEKU424P1
U/UTP Cable Cat.5e, 4x2xAWG24/1, PVC, Eca, grey, Box 305m	69	15	HSEKU424P0
U/UTP Cable Cat.5e, 4x2xAWG24/1, LS0H, Eca, blue, Box 305m	69	15	HSEKU424H1