


Data Sheet for Article: H6ULB02K0B

Patchcord RJ45 unshielded, Cat.6, PVC, blue, 2.0m



SCHRACK-Info

Patchcords for generic, structured network cabling systems. Support all applications requiring Class D to Class E (e.g. 1000Base-T, 100Base-TX, ATM) as well as VoIP, PoE.

Patchcord with moulded boot in matching cable color. Pin assignment 1:1.

ISO/IEC 11801 2nd ed.; EN 50173-1 and IEC 61156-6.

Technical Data

Category	Cat.6
Cable construction	4x2xAWG24/7
Cable shielding	U/UTP
Connection	1:1
Bit rate	up to Gigabit Ethernet
Number of pairs	4
Shielding	unshielded
Cable jacket	PVC
LED Functionality	without LED
Net weight (kg)	0,09
Colour	Blue
Min. ambient temperature (°C)	-20

Technical Data - continued

Max. ambient temperature (°C)	60
RoHS	conform
Patchcordlength (m)	2,0
Net width (mm)	240,00
Net height (mm)	200,00
Connector standard	EN 60603-7
Connector type	RJ45 unshielded
Pin assignment	EIA/TIA 568B 1:1
Packing	Single packed in polybag with label

Article Table

DESCRIPTION	NVP (%)	COPPER WEIGHT (kg/km)	Order No.
Patchcord RJ45 unshielded, Cat.6, PVC, blue, 2.0m			H6ULB02K0B
Optional Accessories			
TOOLLESS LINE Jack RJ45 unshielded, Cat.6 (SFA)			HSEMRJ6UWS
Patchpanel 19" 24xRJ45 unshielded Cat.6, 1U, RAL7035			HSERU246GV
Light grey			
U/UTP Cable Cat.6, 4x2xAWG24/1, 300MHz, LS0H B2ca-s1a,d1,a1 blue, Drum 500m	68	19	HSKU423BP5
U/UTP Cable Cat.6, 4x2xAWG24/1, 300MHz, PVC, Eca, blue Box 305m	69	18	HSEKU423P4
			HSEKU423CP