


Data Sheet for Article: HLP03L002V

FO Pigtail LC, 50/ 125µm OM3, 2.0m, 12 pcs, Class B, colored

PREMIUM



OM3

Technical Data

Net width (mm)	120,00
Net height (mm)	15,00
Net weight (kg)	0,12
Connector standard	IEC 61754-20
Connector type	LC
Fiber	50/125 OM3 Multimode
Insertion loss typical (dB)	0,12
Return loss typical (dB)	≥ 35
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	70
Product	Pigtails
Options	Set of 12
Lenght (mm)	2000
Max. strip length (mm)	1000

Technical Data - continued

Primary coating (µm)	250
Secondary coating (µm)	900
Conductor color (Set of 12) / IEC 60304	red, green, yellow, white, grey, brown, violet, turquoise, black, orange, pink
Fiber standard	IEC 60793-2-10
Plug color	black
Ferrule diameter (mm)	1,25
Plugging cycles	500
Tensile strength (N)	5
Standard	IEC 61753-1

Article Table

DESCRIPTION	Order No.
FO Pigtail LC, 50/125µm OM3, 2.0m, 12 pcs, Class B, colored PREMIUM	HLP03L002V
Optional Accessories	
FO Coupler LC-Duplex, Plastic, Multimode, phosphorbronze without flange, inner shutter, grey, PREMIUM	HMOL000111
FO shrink splice protector 60mm	HELSP00011
FO shrink splice protector 45mm	HELSP00010
FO Splicecassette without cover, without fiber holder stackable, white, PREMIUM	HSELSZSK01
FO splice holder for 6 shrink splice protectors (HELSP0001x) black, suitable for splice cassette HSELSZSK01, PREMIUM	HSELSZSK02
FO splice holder f. 12 shrink splice protectors (HELSP0001x) black, suitable for splice cassette HSELSZSK01, PREMIUM	HSELSZSK05
FO splice cassette cover, white for HSELSZSK01 PREMIUM	HSELSZSK03
FO Splicebox empty for 12 LC-Duplex couplers, 1U, RAL7035 PREMIUM	HSELS240LG
FO Splicebox empty for 24 LC-Duplex couplers, 1U, RAL7035 PREMIUM	HSELS480LG