


Data Sheet for Article: HSELS049CR

FO Splicebox for DIN Rail, 4 Fibers, SC, 9/125µm OS2



RAL7035, incl. Pigtails, incl. couplers, CLASSIC



Technical Data

Net width (mm)	126,00
Net height (mm)	35,20
Netto depth (mm)	155,65
Net weight (kg)	0,59
Fiber	9/125 OS2 Singlemode / G.652.D
Colour	RAL 7035 (Light grey)
Insertion loss typical (dB)	≤0,2
Return loss typical (dB)	≥50
Min. ambient temperature (°C)	-10
Max. ambient temperature (°C)	70
Fibre count	4
Coupler/Connector	SC

Dimensioned drawing: FO Splicebox for DIN Rail, 4 Fibers, SC, 9/125µm OS2



Article Table

DESCRIPTION	Order No.
FO Splicebox for DIN Rail, 4 Fibers, SC, 9/125µm OS2	HSELS049CR
RAL7035, incl. Pigtails, incl. couplers, CLASSIC	
Optional Accessories	
FO shrink splice protector 60mm	HELSP00011
FO shrink splice protector 45mm	HELSP00010
Fiber Optics Cleaning Tool for SC, ST, FC and E2000	HSELSZT002
Suitable for UPC and APC connectors. More than 1,000 cleaning cycles.	
FO Power meter with integrated laser light source (VFL) and	
RJ45-copper cable test. ATTENTION: This is a Laser Class 2 product. Do not stare into the beam. Always keep the cover on the VFL	HSELSZT003
port when not in use. It is recommended to use laser safety glasses when working with fiber optic systems.	
FO Patchcord Duplex SC/UPC - SC/UPC, 9/125µm OS2, 2.0m	
LSOH, yellow	HLP29CC02F

Article Table

DESCRIPTION	Order No.
Optional Accessories	
FO Patchcord Duplex SC/UPC - SC/UPC, 9/125µm OS2, 5.0m LSOH, yellow	HLP29CC05F
FO Patchcord Duplex LC/UPC - SC/UPC, 9/125µm OS2, 2.0m LSOH, yellow	HLP29LC02F
FO Patchcord Duplex LC/UPC - SC/UPC, 9/125µm OS2, 5.0m LSOH, yellow	HLP29LC05F
FO Patchcord Duplex ST/UPC - SC/UPC, 9/125µm OS2, 2.0m LSOH, yellow	HLP29TC02F
FO Patchcord Duplex ST/UPC - SC/UPC, 9/125µm OS2, 5.0m LSOH, yellow	HLP29TC05F
FO Patchcord Duplex SC/UPC - FC/UPC, 9/125µm OS2, 2.0m LSOH, yellow	HLP29CF02F
FO Patchcord Duplex SC/UPC - FC/UPC, 9/125µm OS2, 5.0m LSOH, yellow	HLP29CF05F