

Data Sheet for Article: IKA21530--

Aluminium / Copper terminal, 1-pole green, 185mm²

for copper conductors according to IEC 60947-7-1 and UL 1059, CSA-C22.2 No. 158, for aluminum conductors according to UL 1059, CSA-C22.2 No. 158, note maintenance instructions



Schrack Info

- Distribution block for connecting Al and Cu conductors
- 50mm² up to 300mm² models available
- When using aluminium conductors the common practices for installation must be observed
- Adjust the contact clamps after 6-8 weeks
- Aluminum-terminals for solid round conductors (RE), multi-wire conductors (RM), fine-stranded conductors with end ferrules and also sector conductors (SE and SM)

Technical Data


Netto depth (mm)	73,50
Net width (mm)	37,50
Net weight (kg)	0,03
EAN	9004840594874
Power loss (W)	3,20
Min. ambient temperature (°C)	-25
Max. ambient temperature (°C)	80
Basic Description	Terminal

Datei Tabelle: Aluminium /Copper terminal, 1-pole green, 185mm²

Standards:	IEC 60947-7-1		
Nominal voltage:	1.000VAC/1.000VDC		
Nominal current:	Cu 353A checked with SGS Fimko Ltd		
Rated cross-section:	185mm ²		
Impulse withstand voltage:	8kV		
Pollution degree:	3		
Surge voltage category:	III		
CTI value:	550		
Terminal cross section:	no. of connections: 2 x 185 mm ² (all conductor types)		
	IEC 60947-7-1		
	Cu		
	compact stranded	fine stranded with ferrule	
185mm ²	25Nm	/	
150mm ²		25Nm	
120mm ²			
95mm ²			
70mm ²	/	20Nm	
50mm ²			
35mm ²			
25mm ²			
stripping length	29mm		
allen screw	M18 (SW 10mm)		
Measurement connection:	no. of connections: 1 x 10 mm ² (all conductor types)		
	10mm ²	1,2Nm	/
	6mm ²		1,2Nm
	4mm ²		
	2,5mm ²		
	1,5mm ²		
stripping length	10mm		
screw	M4 (+/-PZ2)		
Werkstoffe:	Terminal body:	Aluminium	tin plated
	Housing:	PA 6 (Halogen-free)	
	Screws:	Steel	zinc plated
Flame resistance:	Self-extinguishing		
Construction:	Fingersafe IP 20		

Datei Tabelle: Aluminium /Copper terminal, 1-pole green, 185mm²

Standards:	IEC 60947-7-1				UL 1059, CSA-C22.2 No. 158			
Nominal voltage:	1.000VAC/1.000VDC				1.000 V AC			
Nominal current:	Cu 353A checked with SGS Fimko Ltd				Cu 310 A, Al 250 A			
Rated cross-section:	185mm2				350 kcmil			
Impulse withstand voltage:	8kV							
Pollution degree:	3							
Surge voltage category:	III							
CTI value:	550				550			
Terminal cross section:		no. of connections: 2 x 185 mm ² (all conductor types)		no. of connections: 2 x 350 kcmil (all conductor types)				
		IEC 60947-7-1		UL 1059, CSA-C22.2 No. 158				
		Cu		Cu		Al		
		compact stranded	fine stranded with ferrule	compact stranded	fine stranded with ferrule	compact stranded		
		185mm2	25Nm	-	350 kcmil	28,2Nm	-	45Nm
150mm2	25Nm	300 kcmi		28,2Nm				
120mm2		250 kcmil						
95mm2		AWG 3/0						
70mm2	-	20Nm	AWG 2/0	-	-			
50mm2			AWG 1/0					
35mm2			AWG 2					
25mm2			AWG 4					
stripping length	29 mm		stripping length	29 mm				
allen screw	M18 (SW 10 mm)		allen screw	M18 (SW 10 mm)				
Measurement connection:		no. of connections: 1 x 10 mm ² (all conductor types)		no. of connections: 1 x AWG8 (all conductor types)				
		10mm2	1,2Nm	-	AWG 8	2,3Nm	-	-
		6mm2		1,2Nm	AWG 10			
		4mm2			AWG 12			
		2,5mm2			AWG 14			
		1,5mm2	-		AWG 16	-		
		stripping length	10mm		stripping length	10 mm		
		screw	M4 (+/-PZ2)		screw	M4 (+/- PZ2)		
Materials:	Terminal body:	Aluminium		tin plated				
	Housing:	PA 6 (Halogen-free)						
	Screws:	Steel		zinc plated				
Flame resistance:		Self-extinguishing						

Dimensioned drawing: Aluminium /Copper terminal, 1-pole green, 185mm²

Article Table

DESCRIPTION	Order No.
Aluminium /Copper terminal, 1-pole green, 185mm ² for copper conductors according to IEC 60947-7-1 and UL 1059, CSA-C22.2 No. 158, for aluminum conductors according to UL 1059, CSA-C22.2 No. 158, note maintenance instructions	
Necessary Accessories	
Contact grease, acid protection acid for Al-conductors 200g 200g tube, Calium fat DIN 51825 K 2 C-40, e.g. for the processing of aluminum	IKAP0200
Optional Accessories	
Aluminium /Copper terminal 185mm ² dust cover for copper conductors according to IEC 60947-7-1 and UL 1059, CSA-C22.2 No. 158, for aluminum conductors according to UL 1059, CSA-C22.2 No. 158, note maintenance instructions	