

Data Sheet for Article: IKB01037N-

N branch terminal, 1-p., 192A, in. 35+70mm², out. 6x16mm²

Input terminal 1x35 + 1x70mm², outgoing terminals 6 x 1.5 - 16mm²



Technical Data

Netto depth (mm)	69,00
Net width (mm)	39,00
Net height (mm)	62,00
Net weight (kg)	0,26
EAN	9004840691689
Power loss (W)	0,30
Basic Description	Terminal
Product standard	EN 60947-7-1
Rated voltage	1000VAC
Current carrying capacity (A)	200A

Technical data

Standards:	IEC 60947-7-1			
current carrying capacity:	Cu 192A			
Rated cross-section:	70mm ²			
Surge voltage resistance:	8kV			
degree of pollution	3			
Overvoltagecategory	III			
CTI value:	550			
Terminal cross section:	no. of connections: 1 x 70mm ² (all conductor types)			
	IEC 60947-7-1		IEC 61238-1	
	Cu		Al	
	compact stranded	stranded with ferrule		
	70mm ²	/	/	
	50mm ²	10Nm		
	35mm ²			
	25mm ²			
	16mm ²			
	10mm ²			
	6mm ²	/	/	
	stripping length	27mm		
	screw	2xM10		
Terminal cross section:	no. of connections: 1 x 35mm ² (all conductor types)			
	IEC 60947-7-1		IEC 61238-1	
	Cu		Al	
	compact stranded	stranded with ferrule		
	35mm ²	/	/	
	25mm ²	6Nm		
	16mm ²			
	10mm ²			
	6mm ²			
	4mm ²			
	2,5mm ²	/	/	
	stripping length	25mm		
	screw	2xM8		
Terminal cross section:	no. of connections: 6 x 16mm ² (all conductor types)			
	16mm ²	/	/	
	10mm ²	2Nm		
	6mm ²			
	4mm ²			
	2,5mm ²			
	1,5mm ²			
	stripping length	12,5mm		
	screw	M6		
	Materials:	Terminal body:	Brass (CuZn39Pb2)	blank
		Housing:	PA 6 (Halogenfree	
		Screws	Steel	zinc plated
	Flame resistance:	Self-extinguishing		
Construction:	Fingersafe IP 20			

DESCRIPTION	Order No.
N branch terminal, 1-p., 192A, in. 35+70mm ² , out. 6x16mm ²	IKB01037N
Input terminal 1x35 + 1x70mm ² , outgoing terminals 6 x 1.5 - 16mm ²	