


Data Sheet for Article: IL162339KK

Aufputz-Zählerverteiler 3A-39H/KTN 6ZP, H1885B810T250mm

6 Meter slots, 2 Meter rows, 4 Downstream rows, 132 Module widths, Front Plate Material Plastic, Carinthia



SCHRACK-Info

- Modular aufgebauter Aufputzverteiler mit Tür und PVC-Rückwand
- Material: 1,25mm pulverbeschichtetes Stahlblech
- Phosphatierter, kunststoffpulverbeschichteter Stahlblechverteiler geprüft und zertifiziert nach EN 62208:2011 und EN 60529:1991, Schutzklasse I für TT/TN und IT Netzform geeignet, schutzisoliert nach ÖVE-IM 12
- Standardmäßig mit Kunststoff-Drehriegelverschluss mit Doppelbartsperre
- Die Ausführung des Vorzählerteils besteht aus einer plombierbaren Abdeckung aus Kunststoff mit montierter Alu/HC Schiene
- Bemessungsspannung Ue: 230/400V/50Hz
- Bemessungsisolationsspannung Ui: 1000V
- Bemessungsstoßspannungsfestigkeit Uimp: 6kV
- Bemessungskurzzeitstromfestigkeit Icw: 25kA / 1s
- Bemessungsstoßstromfestigkeit Ipk: 54kA
- Bedingter Bemessungskurzschlussstrom Icc: 25kA
- Schutzklasse: I
- EMV: EMV Umgebung 1
- komplett bestückt und vorverdrahtet auf Anfrage



Technical Data

Net width (mm)	810,00
Net height (mm)	1.885,00
Netto depth (mm)	250,00
EAN	9004840640847
Power loss (W)	-629,00
Product category	AP-Verteiler mit Zählereinsatz kompl.
Austrian province	Carinthia
Inserts	front plates plastic
Colour	RAL 7035
Meter width	3
HU	39
Meter rows	2
Meter slots	6
IP Rating	IP20C
Downstream rows	4
Front Plate Material	Plastic
Basic Description	Enclosure
Module widths	132

Article Table

DESCRIPTION	Order No.
Aufputz-Zählerverteiler 3A-39H/KTN 6ZP, H1885B810T250mm 6 Meter slots, 2 Meter rows, 4 Downstream rows, 132 Module widths, Front Plate Material Plastic, Carinthia	IL162339KK
Optional Accessories	
Side panels 250mm (1 pair) available for IP20-C and IP54	IL091125
Base front for wall-mounted enclosure U-Profile, width 3 redesigned U-Profile Depth 8mm, 2mm Sheet Steel	IL091300-S
Cam cylinder 61005 for Modul enclosures with 1 key	IL900200-F
Cam cylinder H36000 C/W with 2 keys	IL900202-F
Push through gland plate IP20C, IL001/006/009/036,widths 2-5 W=426 H=130 D=15 mm, Cable glands: 28x 13 mm, 16x 17 mm and 4x 30 mm	IL900102

Article Table

DESCRIPTION	Order No.
Optional Accessories	
Push through gland plate IP20C, 18x 18-30 mm cable glands for IL001/006/009/036 widths 2,3,4,5	IL900105
Wall-mounting brackets for wall-mounted frames M2000 IP20C	IL900020-F
Name strip 1000 mm long, 10 mm high, self-adhesive	BK002401
Blank cover smooth grey RAL 7035, 1000x50x8mm, Empty space cover, 45mm cap dimension, 1 m long, the cover can be shortened individually.	IL900251
Z-metal-installation-cylinder with 2 keys	IL900201-F