

Data Sheet for Article: INSR1340--

Main Switch 3-pole, modular, 40A

Version main switch, Rated current 40A, Poles 3, IP Rating IP40 (front), IP20 (terminals)



Technical Data

Version	main switch
Rated current (A)	40
Poles	3
Mounting	DIN-rail
Standard	IEC 60947, EN 60947, VDE 0660
Rated insulation voltage [Ui] (V)	690
Rated impulse withstand voltage [Uimp] (V)	6000
Rated short-time withstand current Icw	1000
Rated conditional short-circuit-current	10kA @ 440V / 6kA @ 690V
Short-circuit protection maximum fuse	50
Frequency (Hz)	50/60
Operating Current	AC-23A - 400V - 29A AC-3 - 230V - 27A AC-21A - 690V - 40A AC-22A - 690V - 40A AC-23A - 230V - 27A AC-23A - 690V - 17A AC-3 - 400V - 22A AC-3 - 690V - 13A


Technical Data - continued

Switching Capacity	AC-3 - 400V - 11.5kW AC-3 - 690V - 11.5kW AC-23A - 230V - 7.5kW AC-23A - 690V - 15kW AC-23A - 400V - 15kW AC-3 - 230V - 7.5kW
According to UL 508 / CSA	
Connection type	UL/CSA - AWG 14-6
Operating voltage AC (V)	600
Thermal rated continuous current (A)	40
Active Power	1x240VAC - 4Hp 3x120VAC - 5Hp 3x600VAC - 22Hp 3x480VAC - 20Hp 1x120VAC - 2Hp 3x240VAC - 10Hp
Connections	
Conventional thermal current Ith (A)	40
Tightening torque (Nm)	3
Connection cross-section, multi-wire (mm ²)	2,5-16
Connection cross section, single wire (mm ²)	2,5-16
Connection cross-section, flexible wire with ferrule (mm ²)	2,5-16
Retrofit contacts	
Auxiliary contacts	Maximum 2x INSHK001 -- permitted. 1x INSHK001 -- can be snapped on to the left side of the main contact and 1x INSHK001 -- to the right side of the main contact. Maximum configuration 2x NC contact / 2x NO contact. The switching behavior is the same regardless of whether the auxiliary contact is snapped on to the left or right side of the main contact.
Neutral conductor contacts	ATTENTION! If this 3-pole switch is converted to a 4-pole switch using neutral conductor contact INSNK011 --, no additional auxiliary contact can be snapped onto the N contact. On the other side, auxiliary contact INSHK001 -- can be used as normal. For further details, see Auxiliary contact and N contact overview
Operating temperature	-25°C to +55°C
Mechanical durability	100000 switching cycles
Power loss per pole (W)	2,40
Protection against direct contact	finger-proof and back-of-hand-proof according to VDE 0106 Part 100
IP Rating	IP40 (front), IP20 (terminals)
Lockable	With 2 locks, each with a shackle lock diameter of 4-6 mm
Net length (mm)	70,00
Net width (mm)	35,50
Net height (mm)	45,00




Technical Data - continued

Min. ambient temperature (°C)	-25
Max. ambient temperature (°C)	55


Schaltbild INSR1340--



Maßbild INSR1340--



Montageanleitung INSR Hutschiennenmontage Schalter



Montageanleitung INSHK Hilfskontakte bei Verwendung von INSNK Neutraleiterkontakte



Article Table

DESCRIPTION	Order No.
Main Switch 3-pole, modular, 40A	INSR1340
Version main switch, Rated current 40A, Poles 3, IP Rating IP40 (front), IP20 (terminals)	
Optional Accessories	
Auxiliary Contact 1NO/1NC for INSR, INSP and INSA	INSHK001
Nicht für INSE zu verwenden, Version accessories, IP Rating IP20 (terminals)	
N-contact for 3-pole INSR, INSP, and INSA switches, 40-63A	INSNK011
Snap-on N-contact for retrofitting a 3-pole switch to a 4-pole switch. Can only be used with a 40-63A INSR, INSP, or INSA switch.	
Not for use with INSE!	