

Data Sheet for Article: IS503039--

TYTAN TH1, D02 Switch disconnecter, 3+N, with monitoring

main protection, with thermal monitoring, with flashing indicator, with fuse plugs, without fuses



Technical Data

Power loss (W)	7,50
Min. ambient temperature (°C)	-25
Max. ambient temperature (°C)	60
Poles	3+N

Article Table

DESCRIPTION	Order No.
TYTAN TH1, D02 Switch disconnecter, 3+N, with monitoring	IS503039
main protection, with thermal monitoring, with flashing indicator, with fuse plugs, without fuses	
Optional Accessories	
TYTAN HR12 Collective fault message relay 2 C/O, 5A, 250VAC	IS504871

Article Table

DESCRIPTION	Order No.
Optional Accessories	
TYTAN HR11 Single fault message relay 2 C/O, 5A, 250VAC	IS504870
D02-fuse-link 20A, Neozed D02, characteristic gG (gL) blue	IS504035
D02-fuse-link 25A, Neozed D02, characteristic gG (gL) yellow	IS504036
D02-fuse-link 35A, Neozed D02, characteristic gG (gL) black	IS504037
D02-fuse-link 50A, Neozed D02, characteristic gG (gL) white	IS504038
D02-fuse-link 63A, Neozed D02, characteristic gG (gL) copper	IS504039
Adjusting sleeves 20A D02 blue	IS504134
Adjusting sleeves 25A D02 yellow	IS504135
Adjusting sleeves 35A D02 black	IS504136
Adapting D01/D02	ISF90299