

Data Sheet for Article: IU008530-A

Cabinet light IP20 with magnetic fastening and socket, 4W

LED light, luminous flux 560lm, 60.000h, terminal 2.5mm² with cable clamp, with motion detector and I-O-II switch



SCHRACK-Info

- Slim design
- Excellent for cabinets and enclosures with high component density
- Magnetic fastening
- Can be mounted freely in any desired position in metal enclosures
- Electrical socket

I-O-II - switch

- Motion detector
- LED light element
- Long service life (>60.000h)
- Also available:

IU008518---: With screw fastening and socket

IU008531-A: With magnetic fastening and socket type F

Technical Data

Net width (mm)	345,00
Net height (mm)	40,00

Technical Data - continued

Netto depth (mm)	91,00
Net weight (kg)	0,39
Min. ambient temperature (°C)	-40
Max. ambient temperature (°C)	60
IP Rating	IP20
Protection class	I
Rated voltage	230V-AC
Material	Plastic according to UL94 V-0
Colour	RAL 7035 (Light grey)
Width (mm)	345
Height (mm)	40
Depth (mm)	91
Product category	Cabinet light
Rated current (A)	16
Connection type	Screw clamps
Mounting method	Magnetic
Tightening torque (Nm)	0,8
Mounting type	Vertical / Horizontal
Temperature range - Operation (°C)	-40 to +60
Temperature range - Transport/storage (°C)	-40 to +85
Humidity (%)	max. 90
Light source	LED
Power consumption	11W
Luminous flux (lm)	560
Service life	60000

DESCRIPTION	Order No.
Cabinet light IP20 with magnetic fastening and socket, 4W LED light, luminous flux 560lm, 60.000h, terminal 2.5mm ² with cable clamp, with motion detector and I-O-II switch	IU008530-A