

Data Sheet for Article: IU008533--

LED cabinet light, magnet fastening, 80-265 V AC, IP20

with motion detector, connection cable 2m, 2x0.75mm² included



SCHRACK-Info

- Langlebige und wartungsfreie LED-Technologie (50.000h)
- Hervorragend für Schränke und Gehäuse mit hoher Bestückungsdichte
- Magnetbefestigung
- Keinerlei Montageaufwand und frei platzierbar in Stahlschränken
- Weitbereichsspannung AC 85-265V
- Integriertes Netzteil
- Inkludierte Anschlussleitung
- Optional erhältlich: Verlängerungsleitung zur Durchverdrahtung **IU008535**
- Bewegungsmelder

Technical Data

Net width (mm)	330,00
Net height (mm)	35,00
Netto depth (mm)	33,00
Net weight (kg)	0,12
IP Rating	IP20
Rated voltage	85-265V-AC

Technical Data - continued

Material	Plastic
Colour	Transparent
Width (mm)	330
Height (mm)	35
Depth (mm)	33
Product category	Cabinet light
Rated current (A)	2,50
Connection type	Plug-in contact
Mounting method	Magnetic
Tightening torque (Nm)	2
Mounting type	Vertical / Horizontal
Temperature range - Operation (°C)	-20 to +50
Temperature range - Transport/storage (°C)	-20 to +50
Humidity (%)	max. 90
Light source	LED
Power consumption	6W
Luminous flux (lm)	600
Service life	50.000h

Article Table

DESCRIPTION	Order No.
LED cabinet light, magnet fastening, 80-265 V AC, IP20 with motion detector, connection cable 2m, 2x0.75mm ² included	IU008533
Optional Accessories	
Extension cable for IU008533, 2x0,75mm ² , length 1.0m, white	IU008535
Combined MCB/RCD (RCBO) C16/1+N/300mA/Type A Series BOLF, Product category A, Type undelayed, Product standard EN 61009-1:2012 + A12:2006, EN 61009-2-1:1994 + A11:1998	BO817616