

Data Sheet for Article: LI1002020-

LIPSY 30 Dome, LED lights, white, IP44, 3000/4000K

surface-mounted LED wall and ceiling light



Product Details

Mit Ihrem zeitlos, dezenten Design, sind die Wand- und Deckenleuchten der LIPSY DOME Serie beliebte Beleuchtungslösungen für verschiedenste Anwendungsbereiche. Die aus Stahl und einer Acrylglasabdeckung bestehende Leuchten Serie umfasst mehrere Gehäusegrößen. Die breite Abstrahlcharakteristik in Kombination mit dem leistungsstarken LED-Modul, ermöglicht eine homogene Ausleuchtung. Der verbaute Treiber ermöglicht den direkten Anschluss an eine 230V Netzspannung. Die Lichtfarbe des Produktes ist schaltbar zwischen 3000K und 4000K.

Technical Data

Luminous flux (lm)	1600
	1550
Light colour	neutral white
	warm white
Colour temperature (K)	4000
	3000
Colour rendering index (Ra)	≥80
Service life	50000
Dimmable	no
Protection class	I

Technical Data - continued

IP Rating	IP44
Energy efficiency class	E
Shock strength	IK02
Luminaire type	wall luminaires surface mounted ceiling luminaire
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	120
Power (W)	13,50
Operating voltage AC (V)	220-240
Operation current mA (mA)	350
Mounting	surface mounting ceiling surface mounting wall
Colour	White
Material	Aluminum Polycarbonate
Lenght (mm)	300
Width (mm)	300
Height (mm)	93
Diameter (mm)	300
LxWxH mm	300x300x93
ØxH mm	300x93

DESCRIPTION	Order No.
LIPSY 30 Dome, LED lights, white, IP44, 3000/4000K surface-mounted LED wall and ceiling light	LI1002020