

Data Sheet for Article: LI1007236-

I-RING, surface-mounted wall light, 9.2W, 3000K, anthracite



Product Details

Indirect lighting in an organic ring shape summed up: the new I-RING wall light creates flexible and warm-white (3000K) accented lighting in upmarket outdoor areas thanks to its pivoting and rotatable lamp head. It also prevents light pollution as far as possible. The anthracite-coloured outdoor light is optimally protected thanks to its IP65 rating and features an exceptionally long lifespan of 50,000 hours. A well-rounded lighting experience.

Technical Data

Luminous flux (lm)	670
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Service life	50000
Dimmable	no
Protection class	I
Energy efficiency class	D
Shock strength	IK05
Luminaire type	wall luminaires
Illuminant incl.	yes
Lamp holder	LED Platine

Technical Data - continued

Power (W)	9,20
Operating voltage AC (V)	100-240
Operation current mA (mA)	350
Mounting	surface mounting wall
Colour	Anthracite
Material	Aluminum
Length (mm)	240
Height (mm)	240
Diameter (mm)	240
Optional Accessories	LI228753--
LxWxH mm	240x240x82
ØxH mm	240x82

Article Table

DESCRIPTION	Order No.
I-RING, surface-mounted wall light, 9.2W, 3000K, anthracite	LI1007236
Optional Accessories	
Screw set M8, stainless steel	LI228753