

Data Sheet for Article: LI1007290-

MEDO PRO 30, 3000/4000K, 10W, TRIAC C, 110°, black

Recessed floor luminaire



Technical Data

Luminous flux (lm)	3000K=1350lm; 4000K=1350lm
Light colour	neutral white warm white
Colour temperature (K)	4000 3000
Colour rendering index (Ra)	≥90
Glare factor (UGR)	25
Service life	50000
Dimmable	yes trailing edge dimmable (C)
Protection class	I
IP Rating	IP50
Energy efficiency class	C
Shock strength	IK02
Luminaire type	wall luminaires surface mounted ceiling luminaire
Illuminant incl.	yes

Technical Data - continued

Lamp holder	LED Platine
Beam angle (°)	110
Power (W)	10
Operating voltage AC (V)	220-240
Operation current mA (mA)	250
Mounting	surface mounting ceiling surface mounting wall
Colour	Black
Material	Steel Aluminum
Length (mm)	280
Height (mm)	92
Diameter (mm)	280
Optional Accessories	LI1001952-;LI1001950-;LI135250--;LI1001951-;LI135251--;LI135254--
LxWxH mm	280x280x92
ØxH mm	280x92

Article Table

DESCRIPTION	Order No.
MEDO PRO 30, 3000/4000K, 10W, TRIAC C, 110°, black Recessed floor luminaire	LI1007290
Optional Accessories	
MEDO 5m suspension, black	LI1001952
MEDO 5m suspension, white	LI1001950
suspension set for 1-10V MEDO LED, 5-core, black	LI135250
MEDO 5m suspension, grey	LI1001951
suspension set for 1-10V MEDO LED, 5-core, white	LI135251
suspension set for 1-10V MEDO LED, 5-core, silvergrey	LI135254