

Data Sheet for Article: LI1007327-

MEDO 90, 2700/3000/4000K, 79W, TRIAC C, 110°, gray



Technical Data

Luminous flux (lm)	2700K=8300lm; 3000K=8700lm; 4000K=9350lm
Light colour	neutral white warm white
Colour temperature (K)	2700 4000 3000
Colour rendering index (Ra)	≥90
Glare factor (UGR)	22
Service life	50000
Dimmable	yes trailing edge dimmable (C)
Protection class	I
IP Rating	IP50
Energy efficiency class	D
Shock strength	IK02
Luminaire type	surface mounted ceiling luminaire
Illuminant incl.	yes
Lamp holder	LED Platine

Technical Data - continued

Beam angle (°)	110
Power (W)	79
Operating voltage AC (V)	220-240
Operation current mA (mA)	1000
Mounting	surface mounting ceiling
Colour	Grey
Material	Steel Aluminum
Lenght (mm)	900
Height (mm)	92
Diameter (mm)	900
Optional Accessories	LI1001952-, LI1001950-, LI135250--, LI1001951-, LI135251--, LI135254--
LxWxH mm	900x900x92
ØxH mm	900x92

Article Table

DESCRIPTION	Order No.
MEDO 90, 2700/3000/4000K, 79W, TRIAC C, 110°, gray	LI1007327
Optional Accessories	
MEDO 5m suspension, black	LI1001952
MEDO 5m suspension, white	LI1001950
suspension set for 1-10V MEDO LED, 5-core, black	LI135250
MEDO 5m suspension, grey	LI1001951
suspension set for 1-10V MEDO LED, 5-core, white	LI135251
suspension set for 1-10V MEDO LED, 5-core, silvergrey	LI135254