

Data Sheet for Article: LI1007469-

WORKLIGHT PRO 120, 120cm, 4000K, DALI, Touch, white

Pendant luminaire



Product Details

The new WORKLIGHT PRO stands for high performance in the workplace: the DALI-controllable pendant light is optimally designed in line with the latest DIN EN 12464:2021 standard. Its glare-free (UGR<19) luminous efficiency of 127 lm/W, a colour temperature of 4000K and improved, indirect light output offers everything you need for an ergonomic working environment. Dimmability and a long lifespan of 50,000 hours also help to make the office pendant light what it is: a true SLV colleague that assists with productivity.

Technical Data

Luminous flux (lm)	6100
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Glare factor (UGR)	19
Service life	50000
Dimmable	DALI yes Touch DIM
Protection class	I
IP Rating	IP20

Technical Data - continued

Energy efficiency class	D E
Shock strength	IK03
Luminaire type	pendulum luminaire
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	80
Power (W)	50
Operating voltage AC (V)	220-240
Operation current mA (mA)	1200
Mounting	pendant
Colour	White
Material	Steel Aluminum
Length (mm)	1200
Height (mm)	24
Diameter (mm)	32,80
Optional Accessories	EHDALIDIM-
LxWxH mm	1200x33x240
ØxH mm	33x240

Article Table

DESCRIPTION	Order No.
WORKLIGHT PRO 120, 120cm, 4000K, DALI, Touch, white Pendant luminaire	LI1007469
Optional Accessories	
Flush-mounted Dimmer inbox for Dali Ballasts or Drivers For push button control	EHDALIDIM