

Data Sheet for Article: LI1008086-

# ONE LINEAR50 wall-mounted light UP/ DOWN 2700/3000K wh/brass

PHASE



## Technical Data

|                           |                       |
|---------------------------|-----------------------|
| Net length (mm)           | 81,00                 |
| Net width (mm)            | 525,00                |
| Net height (mm)           | 42,00                 |
| Net weight (kg)           | 0,77                  |
| Luminaire type            | wall luminaires       |
| Mounting                  | surface mounting wall |
| Colour                    | Brass<br>White        |
| Material                  | Acryl<br>Aluminum     |
| Beam angle (°)            | 120                   |
| Operating voltage AC (V)  | 220-240               |
| Operation current mA (mA) | 350                   |
| Lamp holder               | LED Platine           |
| Power (W)                 | 14                    |
| Light colour              | warm white            |

## Technical Data - continued

|                             |                            |
|-----------------------------|----------------------------|
| Colour temperature (K)      | 2700<br>3000               |
| Colour rendering index (Ra) | ≥90                        |
| Luminous flux (lm)          | 1000<br>900                |
| Service life                | 50000                      |
| Dimmable                    | trailing edge dimmable (C) |
| Protection class            | I                          |
| IP Rating                   | IP44                       |
| EEC                         | E                          |
| Energy efficiency class     | E                          |
| LxWxH mm                    | 81x525x42                  |

| DESCRIPTION                                                          | Order No. |
|----------------------------------------------------------------------|-----------|
| ONE LINEAR50 wall-mounted light UP/DOWN 2700/3000K wh/brass<br>PHASE | LI1008086 |