

Data Sheet for Article: LI1008598-

PANEL C 625 34 W 830/840 UGR

mounting spring and suspension rope must be ordered separately



Technical Data

Net length (mm)	620,00
Net width (mm)	620,00
Net height (mm)	28,00
Net weight (kg)	2,12
Luminaire type	Recessed ceiling luminaire
Mounting	recessed mounting ceiling
Colour	White
Material	Aluminum
Beam angle (°)	90
Glare factor (UGR)	19
Operating voltage AC (V)	220-240
Operation current mA (mA)	850
Lamp holder	LED Platine
Power (W)	34
Light colour	neutral white warm white
Colour temperature (K)	4000 3000
Colour rendering index (Ra)	≥80

Technical Data - continued

Luminous flux (lm)	4550 4650
Service life	70000
Protection class	II
IP Rating	IP20/54
Mounting Depth mm (mm)	80
LxWxH mm	620x620x28
Cut-out size (mm)	590x590
Cut-out size mm	590x590

Article Table

DESCRIPTION	Order No.
PANEL C 625 34 W 830/840 UGR	LI1008598
mounting spring and suspension rope must be ordered separately	
Necessary Accessories	
PANEL C 4x Mounting springs	LI1008610
PANEL C suspension rope L: 150 cm	LI1008609