

Data Sheet for Article: LI112682--

VERLUX, recessed fitting, LED, 3000K, matt white, 10W

L/B/T 8.5/8.5/4.5 cm



Product Details

Die leichte, eckige Einbauleuchte VERLUX mit rundem Ausschnitt ist in unterschiedlichen Leistungen und Größen erhältlich. Die eckige Deckeneinbauleuchte aus Aluminium ist erhältlich in der Farbe weiß. Der starre Premium LED-Einsatz ermöglicht durch den breitstrahlenden Abstrahlungswinkel von 80° eine homogene Grundbeleuchtung. Aufgrund des im Lieferumfang enthaltenen dimmbaren Konstantstromtreiber ist die Leuchte anschlussfertig für 230 Volt Netzspannung.

Technical Data

Luminous flux (lm)	880
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Service life	35000
Dimmable	yes trailing edge dimmable (C)
Protection class	II
Energy efficiency class	E
Luminaire type	Recessed ceiling luminaire Recessed wall luminaire

Technical Data - continued

Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	80
System efficiency (lm/W)	88
Power (W)	10
Operating voltage AC (V)	220-240
Operation current mA (mA)	500
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø 75
Mounting Depth mm (mm)	45
Colour	White
Material	Aluminum Plastic
Lenght (mm)	85
Width (mm)	85
Height (mm)	45
Weight (kg)	0,15
LxWxH mm	85x85x45
Cut-out size mm	Ø 75

DESCRIPTION	Order No.
VERLUX, recessed fitting, LED, 3000K, matt white, 10W L/B/T 8.5/8.5/4.5 cm	LI112682