

Data Sheet for Article: LI161461--

PL 48 LED, 21W, 3000K, 1800lm, round steel/alu, white

Surface mounted downlight



Product Details

Die Hochvolt LED Deckenleuchte FERA 25 überzeugt durch ihr einfaches klares Design und die hohe Leuchtkraft. Die verbauten LED erreichen einen Lichtstrom von ca. 1800lm. Somit kann die Leuchte bedenkenlos zur allgemeinen Raumbelichtung eingesetzt werden. Dank des eingebauten LED Treibers, ist die Leuchte fertig für den direkten Anschluss an 230V Wechselspannung. Diese Leuchte enthält eingebaute LED-Lampen.



Technical Data

Luminous flux (lm)	1800
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Service life	20000
Dimmable	no
Protection class	I
Energy efficiency class	E

Technical Data - continued

Luminaire type	surface mounted ceiling luminaire
Illuminant incl.	yes
Number of lamps	1
Lamp holder	LED Platine
Beam angle (°)	100
Power (W)	21
Controller	LED driver
Operating voltage AC (V)	220-240
Operation current mA (mA)	550
Mounting	surface mounting ceiling
Colour	White
Material	Aluminum PS
Lenght (mm)	250
Width (mm)	250
Height (mm)	125
Diameter (mm)	250
LxWxH mm	250x250x125
ØxH mm	250x125

DESCRIPTION	Order No.
PL 48 LED, 21W, 3000K, 1800lm, round steel/alu, white Surface mounted downlight	LI161461