

Data Sheet for Article: LI28004430

LCA 35W 24V one4all NF SC EXC2 (DALI-2 DT 6, DSI, switchDIM)

one4all (DALI DT 6, DSI, switchDIM, corridorFUNCTION); Near Field Communication (NFC); Suitable for safety lighting systems in accordance with EN 50172



Technical Data

Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	50
Service life	50.000h
Dimmable	NFC Push to DIM DALI 2
Protection class	II
IP Rating	IP20
Power (W)	35
Controller	Power supply
Input voltage AC (V)	198-264
Input voltage DC (V)	176-280
Output voltage DC (V)	24
Frequency (Hz)	50/60
Colour	White
Material	Plastic

Technical Data - continued

Lenght (mm)	195
Height (mm)	30
Optional Accessories	EHDALIDIM-
LxWxH mm	195x43x30
Dimming range (%)	1 - 100
Voltage range (V)	220-240

Article Table

DESCRIPTION	Order No.
LCA 35W 24V one4all NF SC EXC2 (DALI-2 DT 6, DSI, switchDIM) one4all (DALI DT 6, DSI, switchDIM, corridorFUNCTION); Near Field Communication (NFC); Suitable for safety lighting systems in LI28004430 accordance with EN 50172	
Optional Accessories	
Flush-mounted Dimmer inbox for Dali Ballasts or Drivers For push button control	EHDALIDIM