


Data Sheet for Article: LI70113050

AOT-O ML 42W 4800lm 3000K, IP50 , PMMA opal, white, L-1250mm

Adjustable light output: 27W (3000lm) / 42W (4800lm); 114lm/W



Light distribution curve




Technical Data

Net length (mm)	1.260,00
Net width (mm)	105,00
Net height (mm)	87,00
Net weight (kg)	2,30
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	25
Luminaire type	diffuser luminaire

Technical Data - continued

Mounting	surface mounting ceiling surface mounting wall
Temperature range - Operation (°C)	-20 to +25
Colour	White
Material	PMMA sheetsteel
Cover	opal
Beam angle (°)	120
Glare factor (UGR)	25
Controller	LED driver AC / DC
Operating voltage AC (V)	220-240
Lamp holder	LED Platine
System efficiency (lm/W)	114
Power (W)	42
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Colour stability MacAdam (sdcm)	3
Luminous flux (lm)	3000/4800
Service life	50.000h (L80/B10)
Dimmable	no
Protection class	I
IP Rating	IP50
Shock strength	IK02
LxWxH mm	1260x105x87

Dimensioned drawing: AOT-O ML 42W 4800lm 3000K, IP50 , PMMA opal, white, L-1250mm



Article Table

DESCRIPTION	Order No.
AOT-O ML 42W 4800lm 3000K, IP50 , PMMA opal, white, L-1250mm Adjustable light output: 27W (3000lm) / 42W (4800lm); 114lm/W	LI70113050
Optional Accessories	
Replacement cover for AOT-O L-1260mm	LI44970040