


Data Sheet for Article: LI70123060

AOT-O ML 55W 6600lm 4000K, IP50 , PMMA opal, white, L-1550mm

Adjustable light output: 43W (5100lm) / 55W (6600lm); 120lm/W



Light distribution curve




Technical Data

Net length (mm)	1.560,00
Net width (mm)	105,00
Net height (mm)	87,00
Net weight (kg)	2,70
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	25
Luminaire type	diffuser luminaire

Technical Data - continued

Mounting	surface mounting ceiling surface mounting wall
Temperature range - Operation (°C)	-20 to +25
Colour	White
Material	PMMA sheetsteel
Cover	opal
Beam angle (°)	120
Glare factor (UGR)	25
Controller	LED driver AC / DC
Operating voltage AC (V)	220-240
Lamp holder	LED Platine
System efficiency (lm/W)	120
Power (W)	55
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Colour stability MacAdam (sdcm)	3
Luminous flux (lm)	5100/6600
Service life	50.000h (L80/B10)
Dimmable	no
Protection class	I
IP Rating	IP50
Shock strength	IK02
LxWxH mm	1560x105x87

Dimensioned drawing: AOT-O ML 55W 6600lm 4000K, IP50 , PMMA opal, white, L-1550mm



Article Table

DESCRIPTION	Order No.
AOT-O ML 55W 6600lm 4000K, IP50 , PMMA opal, white, L-1550mm Adjustable light output: 43W (5100lm) / 55W (6600lm); 120lm/W	LI70123060
Optional Accessories	
Replacement cover for AOT-O L-1560mm	LI45000040