


Data Sheet for Article: LIAG0006--

Pole light LOTUS STREET 40W 3000/4000K Ra80 IP66, Ø60mm, bl

asymmetrical, output adjustable max. 40W (100/75/50/30% select), 110lm/W, light colour 2 CCT 3000K/4000K



Light distribution curve



Technical Data

Net height (mm)	526,00
Net diameter (mm)	450,00
Net weight (kg)	7,05
Min. ambient temperature (°C)	-30

Technical Data - continued

Max. ambient temperature (°C)	50
Luminaire type	Mastaufsatzleuchte
Colour	RAL 9017 Traffic black
Operating voltage AC (V)	220-240
Lamp holder	LED Platine
System efficiency (lm/W)	110
Power (W)	12 40 30 20
Light colour	neutral white warm white
Colour temperature (K)	4000 3000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	3300 2200 1320 4400
Service life	80.000h / L80 / B50
Dimmable	no
Protection class	I
IP Rating	IP66
Shock strength	IK08
Illuminant incl.	yes
Diameter (mm)	450
ØxH mm	450x526
Pole-top (mm)	60

DESCRIPTION	Order No.
Pole light LOTUS STREET 40W 3000/4000K Ra80 IP66, Ø60mm, bl asymmetrical, output adjustable max. 40W (100/75/50/30% select), 110lm/W, light colour 2 CCT 3000K/4000K	LIAG0006