


Data Sheet for Article: LID12328--

7820/W LED STRIP 24V DC WW 5m ROLL

4,8W/m IP20 ECONOMY

LED Flexstrip, dimmable, 5 Meter Roll; 08 STRIPS & PROFILES



Product Details

LED light strip, with SMD2216 LEDs, 70LEDs/meter, 4,8W/meter. Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing. Can be cut every 10cm (7-LED segment). Requires 24V DC constant voltage LED driver. Complies with standard EN60598-1 and any other specific standards.



Technical Data

Power per Meter (W/m)	4,90
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥ 90
Service life	50.000h
Dimmable	Depending on driver yes
Protection class	III
IP Rating	IP20

Technical Data - continued

Energy efficiency class	E
Luminaire type	LED Strip
Lamp holder	LED Platine
Beam angle (°)	120
System efficiency (lm/W)	80
Controller	Needs to be ordered separately
Operating voltage DC (V)	24
Mounting	surface mounting ceiling surface mounting wall floor mounting
Length (mm)	5000
Width (mm)	8
Height (mm)	3
Optional Accessories	LID 12344--; LID 12346--;
LxWxH mm	5000x8x3
luminous flux/m (lm/m)	432
Net length (mm)	5.000,00
Net width (mm)	8,00
Net height (mm)	3,00
Net weight (kg)	0,18

Dimensioned drawing: 7820/W LED STRIP 24V DC WW 5m ROLL 4, 8W/m IP20



Article Table

DESCRIPTION	Order No.
7820/W LED STRIP 24V DC WW 5m ROLL 4,8W/m IP20 LED Flexstrip, dimmable, 5 Meter Roll; 08 STRIPS & PROFILES	LID12328
Optional Accessories	
7822 LED STRIP CONNECTOR FOR 7820/7829/7829A/7820V/7835V 8mm 08 STRIPS & PROFILES	LID12344
7824 POWER SUPPLY CABLE FOR 7820/7829/7829A/7820V/7835V 8mm 08 STRIPS & PROFILES	LID12346