

Data Sheet for Article: LID13612--

7880/W DOUBLE LED STRIP 24V WW 5m

ROLL 28,8W/m IP20 €CONOMY

LED Flexstrip, dimmable, 5 Meter Roll; 08 STRIPS & PROFILES



Product Details

Flexible LED light strip, with SMD2835 LEDs, 120LEDs/meter, 28,8W/meter. Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing. Can be cut every 10cm (12-LED segment). Requires 24V DC constant voltage LED driver. Complies with standard EN60598-1 and any other specific standards.



Technical Data

Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥90
Dimmable	Depending on driver yes
Protection class	III
IP Rating	IP20
EEC	F
Energy efficiency class	F

Technical Data - continued

Luminaire type	LED Strip
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	120
System efficiency (lm/W)	78
Controller	Needs to be ordered separately
Operating voltage DC (V)	24
Input voltage DC (V)	24
Mounting	surface mounting ceiling surface mounting wall floor mounting
Material	Plastic
Length (mm)	5000
Width (mm)	20
Height (mm)	3
Optional Accessories	LID13864--;LID13867--;LID13863--;
LxWxH mm	5000x20x3
luminous flux/m (lm/m)	2260

Dimensioned drawing: 7880/W DOUBLE LED STRIP 24V WW 5m ROLL 28,8W/m IP20



Article Table

DESCRIPTION	Order No.
7880/W DOUBLE LED STRIP 24V WW 5m ROLL 28,8W/m IP20 LED Flexstrip, dimmable, 5 Meter Roll; 08 STRIPS & PROFILES	LID13612
Optional Accessories	
7912/AL PROFILE 2m + PC opal diffuser Suitable for LED Strips 7825, 7875, 7880; 08 STRIPS & PROFILES	LID13864
7910/AL PROFILE 2m + PC OPAL DIFFUSER Suitable for LED Strips 7820, 7821, 7830, 7831, 7870; 08 STRIPS & PROFILES	LID13867
7910R/AL RECESSED PROFILE 2m + PC opal diffuser Suitable for LED Strips 7825, 7875, 7880; 08 STRIPS & PROFILES	LID13863