


Data Sheet for Article: LID13849--

Sutil Round2 LED 18W 1260lm 840 IP40 230V

120° white **€ECONOMY**

Recessed downlight, complete with driver




Technical Data

Luminous flux (lm)	1260
Light colour	cool white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Service life	30.000h
Dimmable	no
Protection class	II
IP Rating	IP40
Luminaire type	LED Panel
Illuminant incl.	yes
Number of lamps	1
Lamp holder	LED Platine
Beam angle (°)	120
System efficiency (lm/W)	70

Technical Data - continued

Power Factor	0,9
Power (W)	18
Controller	LED driver
Operating voltage AC (V)	220-240
Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø 210
Mounting Depth mm (mm)	50
Colour	White
Material	Acryl Plastic Die-cast aluminum
Height (mm)	22
Diameter (mm)	223
Optional Accessories	LID16598--
ØxH mm	223x22
Cut-out size mm	Ø 210

Dimensioned drawing: Sutil Round2 LED 18W 1260lm 840 IP40 230V 120° white



Article Table

DESCRIPTION	Order No.
Sutil Round2 LED 18W 1260lm 840 IP40 230V 120° white Recessed downlight, complete with driver	LID13849
Optional Accessories	
89050TLD DALI/PUSH TO DIM/ 1-10V /TRIAC UNIVERSAL DRIVER 50W IP20 230V; 23 DRIVERS	LID16598