

Datenblatt für Artikel: LID14793--

10120G/W/C WHITE 20W CW IP65 230V

complete with driver; 06 DOWNLIGHT FIX LED



Produktinfo

20W LED recessed downlight, IP65. Suitable for Indoor/Outdoor installation. Complete with 500mA driver. Complies with standard EN60598-1 and any other specific standards.

Technische Daten

Luminous flux (lm)	1880
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Dimmable	no
Protection class	II
IP Rating	IP65
Luminaire type	Recessed ceiling luminaire
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	60
System efficiency (lm/W)	94
Power Factor	0,9
Power (W)	20
Controller	LED driver

Technische Daten - Fortsetzung

Operating voltage AC (V)	220-240
Input voltage AC (V)	220-240
Operation current mA (mA)	550
Input current (A)	0,50
Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø 120
Mounting depth (mm)	105
Colour	White
Material	Die-cast aluminum
Diameter (mm)	135
Optional Accessories	LID 16949--
ØxH mm	135x75
Cut-out size mm	Ø 120

Dimensioned drawing: 10120G/W/C WHITE 20W CW IP65 230V



Artikeltabelle

BEZEICHNUNG	BEST.NR.
10120G/W/C WHITE 20W CW IP65 230V complete with driver; 06 DOWNLIGHT FIX LED	LID14793
Optional Accessories	
050180E FAST CABLE CONNECTOR 32A 2x3-port 26 ACCES&GADGETS	LID16949