

Data Sheet for Article: LID15486--

7833/C LED ULTRA THIN STRIP 24VDC CW 5m ROLL 14,4W/m IP20

Requires 24V DC driver; 08 STRIPS & PROFILES



Product Details

Slim Flexible LED light strip, with SMD2110 LEDs, 196LEDs/meter, 14,4W/meter. Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing. Can be cut every 3,5cm (7-LED segment). Requires 24V DC constant voltage LED driver. Complies with standard EN60598-1 and any other specific standards.

Technical Data

Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥90
Dimmable	Depending on driver yes
Protection class	III
IP Rating	IP20
EEC	F
Energy efficiency class	F
Luminaire type	LED Strip
Illuminant incl.	yes
Lamp holder	LED Platine

Technical Data - continued

System efficiency (lm/W)	90
Controller	Needs to be ordered separately
Operating voltage DC (V)	24
Input voltage DC (V)	24
Mounting	surface mounting ceiling surface mounting wall floor mounting
Optional Accessories	LID 14188--
luminous flux/m (lm/m)	1300

Dimensioned drawing: 7833/C LED ULTRA THIN STRIP 24VDC CW 5m ROLL 14,4W/m IP20



Article Table

DESCRIPTION	Order No.
7833/C LED ULTRA THIN STRIP 24VDC CW 5m ROLL 14,4W/m IP20 Requires 24V DC driver; 08 STRIPS & PROFILES	LID15486
Optional Accessories	
20030 REMOTE CONTROL FOR DIMMING LED STRIPS & LAMPS 12/24V for dimming any constant voltage 12V/24V LED fitting including LED strips, LED lamps, LED modules. 50 meters range, 2 memory settings, dimming by touch. 3 channels x 3A; 24 CONTROL & DIMMING	LID14188