

Data Sheet for Article: LID15489--

7887/W STRIP 24V DC WW 5m ROLL 24W/m IP20

Requires 24V DC driver; 08 STRIPS & PROFILES



Product Details

Slim Flexible LED light strip, with SMD2110 LEDs, 700LEDs/meter, 24W/meter. Supplied in 5 meters roll with white PCB and double adhesive tape for a better fixing. Can be cut every 1 cm (7-LED segment). Requires 24V DC constant voltage LED driver. Complies with standard EN60598-1 and any other specific standards.


Technical Data

Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥90
Dimmable	Depending on driver yes
Protection class	III
IP Rating	IP20
EEC	F
Energy efficiency class	F
Luminaire type	LED Strip
Illuminant incl.	yes
Lamp holder	LED Platine

Technical Data - continued

System efficiency (lm/W)	85
Controller	Needs to be ordered separately
Operating voltage DC (V)	24
Input voltage DC (V)	24
Mounting	surface mounting ceiling surface mounting wall floor mounting
Optional Accessories	LID16949--
luminous flux/m (lm/m)	2050

Dimensioned drawing: 7887/W STRIP 24V DC WW 5m ROLL 24W/m IP20



Article Table

DESCRIPTION	Order No.
7887/W STRIP 24V DC WW 5m ROLL 24W/m IP20 Requires 24V DC driver; 08 STRIPS & PROFILES	LID15489
Optional Accessories	
050180E FAST CABLE CONNECTOR 32A 2x3-port 26 ACCES&GADGETS	LID16949