

Data Sheet for Article: LID15780--

38150C/W/C WHITE 24x SPOTS + DIFFUSER

UGR19 40W CW 1200mm

11 OFFICE & KITCHEN



Product Details

40W UGR19 Linear system with diffuser for surface or suspended installation, ideal for offices. Complete with 1000mA driver
Complies with standard EN60598-1 and any other specific standards.

Technical Data

Luminous flux (lm)	3400
Light colour	cool white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥90
Glare factor (UGR)	<19
Dimmable	no
Protection class	I
IP Rating	IP20
Luminaire type	ceiling luminaire pendulum luminaire
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	120

Technical Data - continued

Power of system (W)	85
System efficiency (lm/W)	85
Power Factor	0,9
Power (W)	40
Controller	LED driver
Operating voltage AC (V)	220-240
Operation current mA (mA)	1000
Frequency (Hz)	50/60
Mounting	surface mounting ceiling pendant
Pendant length (mm)	300
Colour	White
Material	Aluminum
Length (mm)	1200
Width (mm)	70
Height (mm)	35
Optional Accessories	LID15782--
LxWxH mm	1200x70x35

Article Table

DESCRIPTION	Order No.
38150C/W/C WHITE 24x SPOTS + DIFFUSER UGR19 40W CW 1200mm 11 OFFICE & KITCHEN	LID15780
Optional Accessories	
050170C/W WHITE CORNER Mounting accessory; FOR 38150A/38151A/38150B/38150BU/38150C; 11 OFFICE & KITCHEN	LID15782