

Data Sheet for Article: LID16355--

62116F/W/W 16W WW IP20 100-240V SURFACE/RECESSED

LED surface-mounted Downlight; 06 DOWNLIGHT FIX LED



Product Details

16W Downlight LED, IP20 Complete with 210mA driver. Complies with standard EN60598-1 and any other specific standards.

Technical Data

Luminous flux (lm)	1500
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Dimmable	no
Protection class	II
IP Rating	IP20
Luminaire type	Recessed ceiling luminaire
Illuminant incl.	yes
Lamp holder	LED Platine
System efficiency (lm/W)	93
Power Factor	0,5
Power (W)	16
Controller	LED driver

Technical Data - continued

Operating voltage AC (V)	100-240
Input voltage AC (V)	100-240
Operation current mA (mA)	210
Input current (A)	0,21
Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø 70-175
Mounting Depth mm (mm)	50
Colour	White
Material	Plastic
Height (mm)	17
Diameter (mm)	235
Optional Accessories	LID16949--
ØxH mm	235x17
Cut-out size mm	Ø 70-175

Dimensioned drawing: 62116F/W/W 16W WW IP20 100-240V SURFACE/RECESSED



Article Table

DESCRIPTION	Order No.
62116F/W/W 16W WW IP20 100-240V SURFACE/RECESSED LED surface-mounted Downlight; 06 DOWNLIGHT FIX LED	LID16355
Optional Accessories	
050180E FAST CABLE CONNECTOR 32A 2x3-port 26 ACCES&GADGETS	LID16949