

Datenblatt für Artikel: LID16688--

50140B/W/D WHITE 40W DL 60x60cm RECESSED PANEL IP20 BACKLIT

Ceiling LED; 06 DOWNLIGHT FIX LED



Produktinfo

60x60 recessed backlit LED panel for T-rail false ceilings. Uniform lighting, ideal for commercial applications. Complete with 850mA driver. Complies with standard EN60598-1 and any other specific standards.

Technische Daten

Luminous flux (lm)	4000
Light colour	cool white
Colour temperature (K)	6000
Colour rendering index (Ra)	≥80
Service life	35.000h
Dimmable	no
Protection class	II
IP Rating	IP20
Luminaire type	LED Panel
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	120
System efficiency (lm/W)	100

Technische Daten - Fortsetzung

Power Factor	0,9
Power (W)	40
Controller	LED driver
Operating voltage AC (V)	220-240
Input voltage AC (V)	220-240
Operation current mA (mA)	850
Input current (A)	0,85
Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Mounting depth (mm)	50
Colour	White
Material	Steel Aluminum
Lenght (mm)	595
Width (mm)	595
Height (mm)	29
Optional Accessories	LID16949--
LxWxH mm	595x595x29

Artikeltabelle

BEZEICHNUNG	BEST.NR.
50140B/W/D WHITE 40W DL 60x60cm RECESSED PANEL IP20 BACKLIT Ceiling LED; 06 DOWNLIGHT FIX LED	LID16688
Optional Accessories	
050180E FAST CABLE CONNECTOR 32A 2x3-port 26 ACCES&GADGETS	LID16949