

Data Sheet for Article: LID16707--

7848/W FLEX TILE 24V DC WW 10W IP20

240x480mm

08 STRIPS & PROFILES



Product Details

Flexible tile, 10W ideal for cover walls and columns. Supplied in 480mmx240mm pcs in white PCB and double adhesive tape for a better fixing. Complete with 2pcs power supply cable and 2pcs tile connectors. Connect max up to 10pcs with one driver. Requires 24V DC constant voltage LED driver. Complies with standard EN60598-1 and any other specific standards.

Technical Data

Luminous flux (lm)	850
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥90
Dimmable	Depending on driver yes
Protection class	III
IP Rating	IP20
Luminaire type	LED Strip
Illuminant incl.	yes
Lamp holder	LED Platine
System efficiency (lm/W)	85

Technical Data - continued

Power (W)	10
Controller	Needs to be ordered separately
Operating voltage DC (V)	24
Input voltage DC (V)	24
Mounting	surface mounting ceiling surface mounting wall floor mounting
Length (mm)	480
Width (mm)	240
Optional Accessories	LID16949--
luminous flux/m (lm/m)	850

Article Table

DESCRIPTION	Order No.
7848/W FLEX TILE 24V DC WW 10W IP20 240x480mm	LID16707
08 STRIPS & PROFILES	
Optional Accessories	
050180E FAST CABLE CONNECTOR 32A 2x3-port	LID16949
26 ACCES&GADGETS	