

Data Sheet for Article: LID17218--

11128G/W/W WHITE RECESSED COB 25W WW 15-45° 230V HONEYCOMB

Complete with 750mA driver; 07 DOWNLIGHT ADJ LED



Product Details

25W COB LED zoomable 15°-45° adjustable downlight with removable honeycomb. Supplied with 600mA driver. Complies with standard EN60598-1 and any other specific standards.

Technical Data

Luminous flux (lm)	2500
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥90
Dimmable	no
Protection class	II
IP Rating	IP20
Luminaire type	Recessed ceiling luminaire
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	15-45
System efficiency (lm/W)	100
Power Factor	0,95

Technical Data - continued

Power (W)	25
Controller	LED driver
Operating voltage AC (V)	220-240
Input voltage AC (V)	220-240
Operation current mA (mA)	600
Input current (A)	0,60
Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Cut-out size (mm)	Ø 120
Mounting Depth mm (mm)	70
Colour	White
Material	Aluminum
Height (mm)	58
Diameter (mm)	134
Optional Accessories	LID16949--
ØxH mm	134x58
Cut-out size mm	Ø 120

Dimensioned drawing: 11128G/W/W WHITE RECESSED COB 25W WW 15-45° 230V HONEYCOMB



Article Table

DESCRIPTION	Order No.
11128G/W/W WHITE RECESSED COB 25W WW 15-45° 230V HONEYCOMB Complete with 750mA driver; 07 DOWNLIGHT ADJ LED	LID17218
Optional Accessories	
050180E FAST CABLE CONNECTOR 32A 2x3-port 26 ACCES&GADGETS	LID16949