

Data Sheet for Article: LID17282--

50140BU/W/V WHITE 40W CCTV 60x60 UGR19 PANEL IP20 BACKLIT

complete with 1000mA driver; 06 DOWNLIGHT FIX LED



Product Details

60x60 adjustable CCT recessed backlit LED panel with microprismatic diffuser for T-rail false ceilings. Uniform lighting, ideal for commercial applications. Complete with 1000mA driver. Complies with standard EN60598-1 and any other specific standards.

Technical Data

Luminous flux (lm)	3600/4000/3800
Light colour	neutral white warm white cool white
Colour temperature (K)	4000 3000 5700
Colour rendering index (Ra)	≥80
Glare factor (UGR)	<19
Dimmable	no
Protection class	II
IP Rating	IP20
Luminaire type	LED Panel

Technical Data - continued

Illuminant incl.	yes
Lamp holder	LED Platine
System efficiency (lm/W)	90
Power Factor	0,90
Power (W)	40
Controller	LED driver
Operating voltage AC (V)	220-240
Input voltage AC (V)	220-240
Operation current mA (mA)	1000
Input current (A)	1
Frequency (Hz)	50/60
Mounting	recessed mounting ceiling
Mounting Depth mm (mm)	60
Colour	White
Material	Steel Aluminum
Lenght (mm)	595
Width (mm)	595
Height (mm)	30
Optional Accessories	LID16949--
LxWxH mm	595x595x30

Article Table

DESCRIPTION	Order No.
50140BU/W/V WHITE 40W CCTV 60x60 UGR19 PANEL IP20 BACKLIT complete with 1000mA driver; 06 DOWNLIGHT FIX LED	LID17282
Optional Accessories	
050180E FAST CABLE CONNECTOR 32A 2x3-port 26 ACCES&GADGETS	LID16949