

Data Sheet for Article: LIEP00026-

Line 40 HL D/I 68W 8582lm 840 MP DALI white l-1411 mm

Pendant luminaire made of aluminium, diffuser PMMA microprismatic, direct/indirect distribution, high output, UGR<19



Technical Data

Lumen	8582
Luminous flux (lm)	8582
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Glare factor (UGR)	<19
Colour stability MacAdam (sdcm)	3
Service life	50.000h / L80 / B10
Dimmable	DALI Push to DIM
Protection class	I
IP Rating	IP20
Luminaire type	pendulum luminaire
Illuminant incl.	yes
Lamp holder	LED Platine
Power (W)	68

Technical Data - continued

Controller	LED driver AC / DC
Operating voltage AC (V)	220-240V 50/60Hz
Operation current mA (mA)	300
Colour	White
Material	Aluminum
Length (mm)	1411
Height (mm)	72
Optional Accessories	EHDALIDIM-
LxWxH mm	1411 x 41 x 72

Article Table

DESCRIPTION	Order No.
Line 40 HL D/I 68W 8582lm 840 MP DALI white l-1411 mm Pendant luminaire made of aluminium, diffuser PMMA microprismatic, direct/indirect distribution, high output, UGR<19	LIEP00026
Optional Accessories	
Flush-mounted Dimmer inbox for Dali Ballasts or Drivers For push button control	EHDALIDIM