

Data Sheet for Article: LIEP00096-

DesignDot 68 12,9W 657lm 930 gold 55° DALI black

Recessed spotlight, reflector gold 55°



Technical Data

Luminous flux (lm)	657
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥90
Colour stability MacAdam (sdcm)	3
Service life	50.000h / L80 / B10
Dimmable	DALI Push to DIM
Protection class	I
IP Rating	IP20
Luminaire type	Recessed ceiling luminaire
Illuminant incl.	yes
Lamp holder	LED Platine
Beam angle (°)	55
Power (W)	12,90
Controller	LED driver AC / DC
Operating voltage AC (V)	220-240V 50/60Hz

Technical Data - continued

Operation current mA (mA)	350
Cut-out size (mm)	Ø 100
Mounting Depth mm (mm)	148
Colour	Black
Material	Die-cast aluminum
Height (mm)	98
Diameter (mm)	78
Optional Accessories	EHDALIDIM-
ØxH mm	78x98
Cut-out size mm	Ø 100

Article Table

DESCRIPTION	Order No.
DesignDot 68 12,9W 657lm 930 gold 55° DALI black Recessed spotlight, reflector gold 55°	LIEP00096
Optional Accessories	
Flush-mounted Dimmer inbox for Dali Ballasts or Drivers For push button control	EHDALIDIM