


Data Sheet for Article: LIEP0480--

NOVIA LINE 50 D/I 34,5W 4430lm 830 MP UGR<19 DALI BL L-1454

Aluminum profile luminaire with microprismatic PMMA diffuser, direct/indirect distribution, incl. cable suspension 2000mm, IP20



Light distribution curve




Technical Data

Net length (mm)	1.454,00
Net width (mm)	50,00
Net height (mm)	81,00
Net weight (kg)	4,40
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	40
Luminaire type	pendulum luminaire

Technical Data - continued

Mounting	Pendant pendulum mounting
Temperature range - Operation (°C)	-20 to +30
Colour	RAL 9005 (black)
Material	Aluminum
Cover	mikroprismatic
Glare factor (UGR)	<19
Controller	LED driver
Operating voltage AC (V)	220-240V
Input voltage AC (V)	220-240V
Lamp holder	LED Platine
System efficiency (lm/W)	7100
Power (W)	68
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥90
Colour stability MacAdam (sdcm)	3
Luminous flux (lm)	7100
Service life	50.000h (L80/B50)
Dimmable	DALI Push to DIM
Protection class	I
IP Rating	IP20
Illuminant incl.	yes
LxWxH mm	1454x50x81

Dimensioned drawing: NOVIA LINE 50 D/I 34, 5W 4430lm 830 MP UGR<19 DALI BL L-1454



Article Table

DESCRIPTION	Order No.
NOVIA LINE 50 D/I 34,5W 4430lm 830 MP UGR<19 DALI BL L-1454 Aluminum profile luminaire with microprismatic PMMA diffuser, direct/indirect distribution, incl. cable suspension 2000mm, IP20	LIEP0480
Optional Accessories	
Flush-mounted Dimmer inbox for Dali Ballasts or Drivers For push button control	EHDALIDIM