

Data Sheet for Article: LIFSX75025

FS 75 Extended (G2) 15W/m 1900lm/m 2500K Ra95 24VDC IP44 10m

10.6 mm wide – can be cut every 5 cm – 140 LEDs/m. Recommended dimming range 10–100%.



Technical Data

Net length (mm)	10.000,00
Net width (mm)	11,00
Net height (mm)	3,00
Net weight (kg)	0,32
Luminaire type	LED Strip
Temperature range - Operation (°C)	-20 to +45
Beam angle (°)	120
Operating voltage DC (V)	24
System efficiency (lm/W)	130
Light colour	ultra warm white
Colour temperature (K)	2500
Colour rendering index (Ra)	≥95
Colour stability MacAdam (sdcm)	3
luminous flux/m (lm/m)	1900
Dimmable	Depending on driver yes

Technical Data - continued

Protection class	III
IP Rating	IP44
Energy efficiency class	D
Illuminant incl.	yes
LxWxH mm	10000x11x3

DESCRIPTION	Order No.
FS 75 Extended (G2) 15W/m 1900lm/m 2500K Ra95 24VDC IP44 10m 10.6 mm wide – can be cut every 5 cm – 140 LEDs/m. Recommended dimming range 10–100%.	LIFSX75025