

Data Sheet for Article: LIG5L03221


AVENIDA Pole LED 14W 1180lm 730 IP66 IK09

1000mm graphite

Bollar luminaire, rotationally symmetric



Light distribution curve




Technical Data

Net height (mm)	1.000,00
Net diameter (mm)	150,00
Net weight (kg)	9,70
Min. ambient temperature (°C)	-40
Max. ambient temperature (°C)	50

Technical Data - continued

Mounting	floor mounting
Colour	Grafit
Material	Die-cast aluminum
Operating voltage AC (V)	220-240
Lamp holder	LED Platine
Power (W)	14
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥70
Luminous flux (lm)	1180
Service life	96.000h / L80 / B10
Dimmable	no
Protection class	II
IP Rating	IP66
Illuminant incl.	yes
Diameter (mm)	150
ØxH mm	150x1000
Numbers of luminars per MCB B16	50

Dimensioned drawing: AVENIDA Pole LED 14W 1180lm 730 IP66 IK09 1000mm graphite



DESCRIPTION	Order No.
AVENIDA Pole LED 14W 1180lm 730 IP66 IK09 1000mm graphite Bollar luminaire, rotationally symmetric	LIG5L03221