

Data Sheet for Article: LIGA25727A

AVENIDA LED 25W 3000lm 727 IP66 asymm. graphite

Pole-top luminaire, the mast is not part of the luminaire



Technical Data

Net height (mm)	482,00
Net diameter (mm)	360,00
Net weight (kg)	4,40
Min. ambient temperature (°C)	-45
Max. ambient temperature (°C)	55
Luminaire type	street light
Surge protection (kV)	6
Mounting	mast mounting
Colour	Grafit
Material	Polycarbonate Die-cast aluminum
Cover	Clear
Controller	ECG
Operating voltage AC (V)	220-240

Technical Data - continued

Lamp holder	LED Platine
System efficiency (lm/W)	120
Power (W)	25
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥70
Luminous flux (lm)	3000
Service life	100.000h / L90 / B10
Dimmable	no
Protection class	II
IP Rating	IP66
Shock strength	IK10
Illuminant incl.	yes
Pole-top (mm)	76
Wind Exposed (m²)	0,088
Diameter (mm)	360
ØxH mm	360x482
Numbers of luminars per MCB B10	15
Numbers of luminars per MCB B16	21

Article Table

DESCRIPTION	Order No.
AVENIDA LED 25W 3000lm 727 IP66 asymm. graphite Pole-top luminaire, the mast is not part of the luminaire	LIGA25727A
Optional Accessories	
Cover masking for pole ø60 mm for AVENIDA LED, graphite	LIG7500982