

Data Sheet for Article: LIGA348275

AVENIDA LED 34W 3950lm 827 IP66

rotationally symm. graphite

Pole-top luminaire, the mast is not part of the luminaire



Technical Data

Net height (mm)	482,00
Net diameter (mm)	360,00
Net weight (kg)	4,40
Min. ambient temperature (°C)	-40
Max. ambient temperature (°C)	50
Luminaire type	street light
Surge protection (kV)	6
Mounting	mast mounting
Colour	Grafit
Material	Polycarbonate Die-cast aluminum
Cover	opal Clear
Controller	ECG

Technical Data - continued

Operating voltage AC (V)	220-240
Lamp holder	LED Platine
Power (W)	34
Light colour	warm white
Colour temperature (K)	3000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	4250
Service life	100.000h / L80 / B10
Dimmable	no
Protection class	II
IP Rating	IP66
Shock strength	IK08
Illuminant incl.	yes
Pole-top (mm)	76
Wind Exposed (m²)	0,088
Diameter (mm)	360
ØxH mm	360x482
Numbers of luminars per MCB B10	15
Numbers of luminars per MCB B16	21

Article Table

DESCRIPTION	Order No.
AVENIDA LED 34W 3950lm 827 IP66 rotationally symm. graphite Pole-top luminaire, the mast is not part of the luminaire	LIGA34827S
Optional Accessories	
Cover masking for pole ø60 mm for AVENIDA LED, graphite	LIG7500982