


AURA 2 LED 11W 920lm 4000K IP43

wall- & ceiling luminaire with three-layer glass TRIPLEX



Light distribution curve



Technische Daten

Net height (mm)	120,00
Net diameter (mm)	280,00
Net weight (kg)	1,50
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	25
Luminaire type	wall luminaires surface mounted ceiling luminaire

Technische Daten - Fortsetzung

Mounting	surface mounting ceiling surface mounting wall
Colour	White
Material	Glass Metal
Beam angle (°)	180
Controller	LED driver
Operating voltage AC (V)	230
Lamp holder	LED Platine
System efficiency (lm/W)	84
Power (W)	11
Light colour	neutral white
Colour temperature (K)	4000
Colour rendering index (Ra)	≥80
Luminous flux (lm)	920
Number of lamps	1
Service life	67.000h / L80 / B10
Protection class	I
IP Rating	IP43
Illuminant incl.	yes
Diameter (mm)	280
ØxH mm	280x120

Artikeltabelle

BEZEICHNUNG	BEST.NR.
AURA 2 LED 11W 920lm 4000K IP43 wall- & ceiling luminaire with three-layer glass TRIPLEX	LIOSM51723
Optional Accessories	
AURA 2 spare glass	LIOSM20002