


Data Sheet for Article: LITP0099--

LEILA II LED 12/17/23W 1304/1847/2500lm CCT 230V IP65 white

Wall and ceiling luminaire for outdoor use; adjustable wattage and color temperature;
3000/4000/6000K; 12W = 1304 lm / 17W = 1847 lm / 23W = 2500 lm at 4000K;
108 lm/W at 4000K, Ø 320 mm




Light distribution curve



Technical Data

Net height (mm)	65,00
Net diameter (mm)	320,00
Net weight (kg)	0,80
Min. ambient temperature (°C)	-20
Max. ambient temperature (°C)	40
Luminaire type	wall luminaires surface mounted ceiling luminaire
Mounting	surface mounting
Temperature range - Operation (°C)	-20 to +40
Colour	White
Beam angle (°)	120
Input voltage AC (V)	220-240
Input voltage DC (V)	300-330
Power (W)	12 23 17
Light colour	neutral white warm white
Colour temperature (K)	4000 3500 3000
Colour rendering index (Ra)	80
Colour stability MacAdam (sdcm)	5
Luminous flux (lm)	2500
Service life	50000
Dimmable	no
Protection class	II
IP Rating	IP65
Shock strength	IK10
Diameter (mm)	320
ØxH mm	320x65

Dimensioned drawing: LEILA II LED 12/17/23W 1304/1847/2500lm CCT 230V IP65 white



DESCRIPTION	Order No.
LEILA II LED 12/17/23W 1304/1847/2500lm CCT 230V IP65 white	
Wall and ceiling luminaire for outdoor use; adjustable wattage and color temperature; 3000/4000/6000K; 12W = 1304 lm / 17W = 1847 lm / 23W = 2500 lm at 4000K; 108 lm/W at 4000K, Ø 320 mm	LITP0099