

Data Sheet for Article: MGF59050-A

Ammeter, 96x96mm, 50A, AC, Direct measuring

Direct measurement, Type Front mounting, Function ammeter AC, Size 96x96mm, Measuring range 50A, IP Rating IP52 (front), IP00 (connections)



Technical Data

Standard	EN 50081 BS-89 VDE 0410 EN 60051 EN 50082 EN 61010
Type	Front mounting
Display technology	analog
Measuring range	50A
Size	96x96mm
Frequency range	15-100Hz
Accuracy	1,50 percent
Operating voltage AC (V)	600
Overload (continuous)	1,5 In
Overload (short-time)	5 In 30s, 10 In 5s, 40 In 1s
Isolation test voltage	2 kV R.M.S 50 Hz/1 min


Technical Data - continued

Reference temperature (°C)	+10 bis +30
Temperature range - Transport/storage (°C)	-25 to +40
Power loss (W)	1,20
Mounting method	Instrument for vertical mounting
IP Rating	IP52 (front), IP00 (connections)
Burden	0,4VA
Vibration resistance	VDE 0410, 2,5g, ±0,25mm, 50Hz
shock resistance	VDE 0410, 15G

Circuit diagram: Ammeter, 96x96mm, 50A, AC, Direct measuring



Dimensioned drawing: Ammeter, 96x96mm, 50A, AC, Direct measuring



DESCRIPTION	Order No.
Ammeter, 96x96mm, 50A, AC, Direct measuring	
Direct measurement, Type Front mounting, Function ammeter AC, Size 96x96mm, Measuring range 50A, IP Rating IP52 (front), IP00 (connections)	MGF59050-A